

Safety Data Sheet

haupa®

HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Company name:	HAUPA GmbH & Co.KG	
Street:	Königstraße 165-169	
Place:	D-42853 Remscheid	
Telephone:	+49 (2191) 84 18-0	Telefax: +49 (2191) 84 18 840
e-mail:	sales@haupa.com	
Contact person:	Jochen Husli	Telephone: +49 (2191) 84 18-0
e-mail:	jochen.husli@haupa.com	
Internet:	www.haupa.com	
Responsible Department:	Sicherheitsdatenblätter / Datenmanagement	

1.4. Emergency telephone number:

Die Nummer der Gesellschaft ist nur zu Bürozeiten besetzt: +49 (2191) 84 18-0(7:00 - 16:30 Uhr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Aerosol: Aerosol 1
Skin corrosion/irritation: Skin Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Aspiration hazard: Asp. Tox. 1
Hazardous to the aquatic environment: Aquatic Chronic 2
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.
Causes skin irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Signal word: Danger

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Safety Data Sheet



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 2 of 9

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Process vapors can irritate airways, skin and eyes.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	80 -< 90 %		
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
75-28-5	isobutane	2,5 -< 10 %		
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1; H220			
124-38-9	Carbon dioxide	2,5 -< 10 %		
	204-696-9			
74-98-6	propane	< 2,5 %		
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

>= 30 % aliphatic hydrocarbons.

Further Information

Labelling for contents according to regulation (EC) No 648/2004, annex 7:
aliphatic hydrocarbons > 30%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. Seek medical attention if problems persist.

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 3 of 9

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Caution if victim vomits: Risk of aspiration! Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur: difficulties of breathing. Headache.

4.3. Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration! In all cases of doubt, or when symptoms persist, seek medical advice.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂). Dry extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition. - No smoking. Flammable vapours can accumulate in head space of closed systems.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Safety Data Sheet



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 4 of 9

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

No data available

Further information on storage conditions

Protect against: heat.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
124-38-9	Carbon dioxide	5000	9150		TWA (8 h)	WEL
		15000	27400		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

Additional advice on limit values

none

8.2. Exposure controls

Appropriate engineering controls

Do not eat, drink, smoke or sneeze at the workplace.

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Protect skin by using skin protective cream.

Hand protection: NBR (Nitrile rubber).

Thickness of glove material: 0,45 mm

penetration time (maximum wearing period): 240 min

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter type: AX (for group 2 low boilers). In case of a maximum contaminant concentration in inhaled air of 1000 mL/m³ (0.1 % by vol.), group 2 may be used for a maximum of 60 min. In case of a maximum contaminant concentration in inhaled air of 5000 mL/m³ (0.5 % by vol.), group 2 may be used for a maximum of 20 min.

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 5 of 9

Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	colourless
Odour:	like: Benzine

Test method**Changes in the physical state**

Lower explosion limits:

Upper explosion limits:

Ignition temperature:

> 200 °C

Density (at 20 °C):

ca. 0,705 g/cm³

Water solubility:

Immiscible

Solvent content:

96,6%

9.2. Other information

Solid content:

0%

SECTION 10: Stability and reactivity**10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors. Carbon dioxide. Carbon monoxide. aldehydes

Further information

In case of exceeding the storage temperature: Danger of bursting container.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 6 of 9

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64742-49-0	Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50	> 2000 mg/kg	rat	
	dermal	LD50	> 2000 mg/kg	rabbit	
	inhalative (4 h) aerosol	LC50	> 5 mg/l	rat	

Irritation and corrosivity

Causes skin irritation.

Irritant effect on the eye: Not an irritant.

Has degreasing effect on the skin.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information
12.1. Toxicity

Leakage into the environment must be prevented.

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
64742-49-0	Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane					
	Acute crustacea toxicity	EC50	1 - 10 mg/l	48 h	daphnia	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Toxic to aquatic organisms.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36

12.4. Mobility in soil

If product enters soil, it will be mobile and may contaminate groundwater.

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

Toxic to fish.

Further informationDoesn't get into the sewage water as long as the process is carried out according to regulations.
hazardous to water (WGK 2)

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 7 of 9

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Consult the appropriate authorities about waste disposal. Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Consult the appropriate authorities about waste disposal. Dispose of waste according to applicable legislation.
Cleaned containers may be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Transport category: 2
 Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1

Safety Data Sheet

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 8 of 9



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)
E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
EmS: F-D, S-U

Other applicable information (marine transport)
E0

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)
E0
: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Naphtha (petroleum), hydrotreated light; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Safety Data Sheet



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro-Motoren-Reiniger "HUPelctroClean" Aerosol 500ml

Print date: 23.03.2016

Product code: 170114

Page 9 of 9

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

Other applicable information

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):

VOC-value (in g/L): 681,6

Volatile organic compounds (VOC) content in percent by weight: 96,6

National regulatory information

Water contaminating class (D):

2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)