

HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning agent.

1.3. Details of the supplier of the safety data sheet

Company name: HAUPA GmbH & Co.KG
Street: Königstraße 165-169
Place: D-42853 Remscheid

Telephone: +49 (2191) 84 18-0 Telefax: +49 (2191) 84 18 840

e-mail: sales@haupa.com

Contact person: Jochen Husli Telephone: +49 (2191) 84 18-0

e-mail: jochen.husli@haupa.com

Internet: www.haupa.com

Responsible Department: Sicherheitsdatenblätter / Datenmanagement

1.4. Emergency telephone Die Nummer der Gesellschaft ist nur zu Bürozeiten besetzt: +49 (2191) 84

<u>number:</u> 18-0(7:00 - 16:30 Uhr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories: Aerosol: Aerosol 3

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

acetone; propan-2-one; propanone **Signal word:** Warning

Pictograms:



Hazard statements

H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 2 of 8

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

5 % by mass of the contents are flammable.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Do not breathe aerosol. Contains refrigerated gas; may cause cryogenic burns or injury.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture related information

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]					
811-97-2	norflurane, 1,1,1,2-tetrafluoroethan	orflurane, 1,1,1,2-tetrafluoroethane (R134a)				
	212-377-0		01-2119459374-33			
67-64-1	-1 acetone; propan-2-one; propanone					
	200-662-2	606-001-00-8	01-2119471330-49			
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066					

Full text of H and EUH statements: see section 16.

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % aliphatic hydrocarbons.

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Caution if victim vomits: Risk of aspiration! Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 3 of 8

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2). Dry extinguishing powder. Foam.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use only in well-ventilated areas.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Protect against: heat. UV-radiation/sunlight.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

haupa

HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 4 of 8

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
811-97-2	1,1,1,2-Tetrafluoroethane (HFC 134a)	1000	4240		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance						
DNEL type		Exposure route	Effect	Value			
67-64-1	acetone; propan-2-one; propanone						
Consumer DNE	EL, long-term	oral	systemic	62 mg/kg bw/day			

PNEC values

CAS No	Substance				
Environmental compartment Value					
67-64-1 acetone; propan-2-one; propanone					
Air		21 mg/l			

8.2. Exposure controls

Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Required properties: cold resistant.

Protect skin by using skin protective cream. Hand protection: NBR (Nitrile rubber). DIN EN 374

Skin protection

Body protection: not required.

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
Colour: colourless
Odour: characteristic

Test method

Changes in the physical state

Lower explosion limits: 2,1 vol. %
Upper explosion limits: 13 vol. %
Ignition temperature: 500 °C



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 5 of 8

Vapour pressure:

6000 hPa

(at 20 °C)

Density (at 20 °C):

1,17 g/cm³

Water solubility:

Immiscible

Solvent content:

5%

9.2. Other information

Solid content: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

Further information

Danger of bursting container. >50°C

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name						
	Exposure routes	Method	Dose	Species	Source		
67-64-1	acetone; propan-2-one; propanone						
	oral	LD50	5800 mg/kg	Rat	RTECS		
	dermal	LD50	20000 mg/kg	Rabbit	IUCLID		
	inhalative (4 h) vapour	LC50	76 mg/l	Rat			

Irritation and corrosivity

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 6 of 8

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Global Warming potential (GWP): 1300 1,1,1,2,- Tetrafluorethan

CAS No	Chemical name							
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source		
67-64-1	acetone; propan-2-one; propanone							
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss			
	Acute crustacea toxicity	EC50	6100 mg/l	48 h	Daphnia magna			

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Doesn't get into the sewage water as long as the process is carried out according to regulations.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances

Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded

chemicals; gases in pressure containers (including halons) containing hazardous substances

Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

haupa

HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 7 of 8

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity:1 LExcepted quantity:E0Transport category:2Tunnel restriction code:D

Inland waterways transport (ADN)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1



Classification code: 5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number:UN 195014.2. UN proper shipping name:AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1



Special Provisions: 63, 190, 277, 327, 344, 959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es): 2.1



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Elektro+Kontaktreiniger "HUPcontactXtra" Aerosol 400ml

Print date: 23.03.2016 Product code: 170120 Page 8 of 8

14.4. Packing group:

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

Other applicable information

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): Volatile organic compounds (VOC) content in percent by weight: 100

VOC-value (in g/L): 1170

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour. H229 Pressurised container: May burst if heated.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)