

Safety Data Sheet

haupa®

HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Lubricant, lubricants and release products

1.3. Details of the supplier of the safety data sheet

Company name:	HAUPA GmbH & Co.KG	
Street:	Königstraße 165-169	
Place:	D-42853 Remscheid	
Telephone:	+49 (2191) 84 18-0	Telefax: +49 (2191) 84 18 840
e-mail:	sales@haupa.com	
Contact person:	Jochen Husli	Telephone: +49 (2191) 84 18-0
e-mail:	jochen.husli@haupa.com	
Internet:	www.haupa.com	
Responsible Department:	Sicherheitsdatenblätter / Datenmanagement	

1.4. Emergency telephone number:

Die Nummer der Gesellschaft ist nur zu Bürozeiten besetzt: +49 (2191) 84 18-0(7:00 - 16:30 Uhr)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:
Aerosol: Aerosol 1
Aspiration hazard: Asp. Tox. 1
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 2 of 8

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

2.3. Other hazards

Wear suitable gloves.

SECTION 3: Composition/information on ingredients
3.2. Mixtures**Hazardous components**

CAS No	Chemical name	EC No	Index No	REACH No	Quantity
		Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified				25 - < 50 %
	265-149-8	649-422-00-2		01-2119484819-18	
	Asp. Tox. 1; H304 EUH066				
75-28-5	isobutane				10 - < 25 %
	200-857-2	601-004-00-0		01-2119485395-27	
	Flam. Gas 1; H220				
74-98-6	propane				10 - < 25 %
	200-827-9	601-003-00-5		01-2119486944-21	
	Flam. Gas 1; H220				
106-97-8	butane				2,5 - < 10 %
	203-448-7	601-004-00-0		01-2119474691-32	
	Flam. Gas 1; H220				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures
4.1. Description of first aid measures**General information**

Remove contaminated, saturated clothing immediately.

After inhalation

Provide fresh air. Seek medical attention if problems persist.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Caution if victim vomits: Risk of aspiration! Medical treatment necessary.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

Caution if victim vomits: Risk of aspiration!

SECTION 5: Firefighting measures
5.1. Extinguishing media

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 3 of 8

Suitable extinguishing mediaCarbon dioxide (CO₂). Dry extinguishing powder. Foam.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

In case of fire and/or explosion do not breathe fumes.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Treat the recovered material as prescribed in the section on waste disposal.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use only in well-ventilated areas. Keep away from sources of ignition. - No smoking. Flammable vapours can accumulate in head space of closed systems.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours may form explosive mixtures with air.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.

Further information on storage conditions

Protect against: heat. UV-radiation/sunlight.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 4 of 8

8.2. Exposure controls
Protective and hygiene measures

Work in well-ventilated zones or use proper respiratory protection. Do not eat, drink, smoke or sneeze at the workplace.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Protect skin by using skin protective cream.

Hand protection: NBR (Nitrile rubber).

Thickness of glove material: 0,7mm

penetration time (maximum wearing period): 240min

Skin protection

Body protection: not required.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Filter respirator (DIN EN 147). AX

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	odourless

Test method
Changes in the physical state

Initial boiling point and boiling range: - 44 °C

Lower explosion limits:

Upper explosion limits:

Ignition temperature: > 200 °C

Density (at 20 °C): 0,71745 g/cm³

Solvent content: 81,3 %

9.2. Other information

Solid content: No data available

SECTION 10: Stability and reactivity
10.1. Reactivity

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Reaction takes place at temperatures above: 50°C

10.5. Incompatible materials

Oxidizing agents, strong.

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 5 of 8

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. aldehydes.

Further information

Danger of bursting container. >50°C

SECTION 11: Toxicological information
11.1. Information on toxicological effects
Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64742-47-8	Distillates (petroleum), hydrotreated light, Kerosine - unspecified				
	oral	LD50	> 2000 mg/kg	Rat	
	dermal	LD50	> 2000 mg/kg	Rabbit	
	inhalative (4 h) aerosol	LC50	> 5 mg/l	Rat	
106-97-8	butane				
	inhalative (4 h) gas	LC50	658 ppm	Rat	GESTIS

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information
12.1. Toxicity

There are no data available on the mixture itself.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89

12.4. Mobility in soil

No data available

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 6 of 8

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No data available

Further information

Doesn't get into the sewage water as long as the process is carried out according to regulations.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Dispose of waste according to applicable legislation.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -

Safety Data Sheet



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 7 of 8

Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

No data available

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

Other applicable information

Transport as "limited quantity" according to chapter 3.4 ADR/RID.

Safety Data Sheet



HAUPA GmbH & Co.KG

according to Regulation (EC) No 1907/2006

Allround Spray mit PTFE "HUPptfeSynt" Aerosol 400ml

Print date: 23.03.2016

Product code: 170160

Page 8 of 8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC):

VOC-value (in g/L): 583,2

Volatile organic compounds (VOC) content in percent by weight: 81,29

National regulatory information

Water contaminating class (D):

1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)