

6 tonne pressing tools

Tool	Article No.	Type	Insert range	Pressing width	Sensor technology	Pressing width thorn	Pressing force kN	Working pressure in bar	Head can be opened	Quick coupling	HUB/ opening mm	Pressing range for cable lugs						Pressing range for connectors						Dual piston pump	kg	Set kg	Battery	Pressing time in sec.	
												Cu	Cu DIN	F-Type	Al DIN	CU standard PL	CU standard light T	Cu	Cu DIN	F-Type	Al DIN	Cu standard PL	Cu standard light M						
	215765	HHs-6	185 H6	slim	-	-	60	700	●	-	17	10 - 240	10 - 185	-	10 - 185	10 - 185	-	10 - 185	10 - 185	-	10 - 185	10 - 185	-	●	3,000	7,900	-	-	
	215770	SHs-6	185 H6	slim	-	-	60	700	●	-	17	10 - 240	10 - 185	-	16 - 150	10 - 240	-	10 - 240	10 - 240	-	16 - 185	10 - 240	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	215770/M	SHs-6	185 H6	slim	●	-	60	700	●	-	17	10 - 240	10 - 185	-	16 - 185	10 - 240	-	10 - 240	10 - 240	-	16 - 185	10 - 240	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	215800	HH-6	240 H6	slim	-	-	60	700	●	-	17	10 - 240	10 - 240	-	16 - 185	10 - 240	-	10 - 240	10 - 240	-	16 - 185	10 - 240	-	●	3,000	4,500	-	-	
	215881	SH-6	240 H6	slim	-	-	60	700	●	-	17	10 - 240	10 - 240	-	16 - 185	10 - 240	-	10 - 240	10 - 240	-	16 - 185	10 - 240	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	215881/M	SH-6	240 H6	slim	●	-	60	700	●	-	17	10 - 240	10 - 240	-	16 - 185	10 - 240	-	10 - 240	10 - 240	-	16 - 185	10 - 240	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	216807	KO-6	300 O6	slim	-	-	60	700	●	●	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	-	-	3,200	4,200	-	-	
	216804	MO-6	300 O6	slim	-	-	60	700	●	-	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	-	-	8,100	11,800	-	-	
	215802	HO-6	300 O6	slim	-	-	60	700	●	-	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	●	-	3,500	5,000	-	-	
	215801	SO-6	300 O6	slim	-	-	60	700	●	-	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	215801/M	SO-6	300 O6	slim	●	-	60	700	●	-	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	-	-	2,400	7,900	Li-Ion 18V 1,5 Ah	5	
	216800/M	A0-6	300 O6	slim	●	-	60	700	●	-	17	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	6 - 300	6 - 300	6 - 240	6 - 300	6 - 300	●	-	4,500	9,500	Li-Ion 18V 3 Ah	4	
	216665	KD300-6		wide	-	●	60	700	-	●	-	16 - 300	-	16 - 240	-	16 - 300	16 - 300	16 - 120	16 - 300	16 - 95	-	16 - 120	16 - 120	-	-	2,800	3,800	-	-
	216660	HD300-6		wide	-	●	60	700	-	-	-	16 - 300	-	16 - 240	-	16 - 300	16 - 300	16 - 120	16 - 300	16 - 95	-	16 - 120	16 - 120	●	-	5,000	6,500	-	-
	216663/M	AD300-6		wide	●	●	60	700	-	-	-	16 - 300	-	16 - 240	-	16 - 300	16 - 300	16 - 120	16 - 300	16 - 95	-	16 - 120	16 - 120	-	-	4,500	9,500	Li-Ion 18V 1,5 Ah	6
	216666	KD400-6		wide	-	●	60	700	●	●	-	25 - 400	-	25 - 400	-	25 - 400	25 - 400	25 - 400	25 - 400	25 - 400	-	25 - 400	25 - 400	-	-	3,000	4,000	-	-
	216661	HD400-6		wide	-	●	60	700	●	-	-	25 - 400	-	25 - 400	-	25 - 400	25 - 400	25 - 400	25 - 400	25 - 400	-	25 - 400	25 - 400	●	-	5,200	6,700	-	-
	216667/M	AD400-6		wide	●	●	60	700	●	-	-	25 - 400	-	25 - 400	-	25 - 400	25 - 400	25 - 400	25 - 400	25 - 400	-	25 - 400	25 - 400	-	-	4,800	9,800	Li-Ion 18V 1,5 Ah	6
	216669/M	SDE240-6		wide	●	●	60	700	●	-	-	6 - 240	-	6 - 240	-	6 - 240	6 - 240	6 - 240	6 - 240	6 - 240	-	6 - 240	6 - 240	-	-	2,900	7,900	Li-Ion 18V 1,5 Ah	5