

T-Steckschlüssel 1000 V

aus Vanadium-Molybdän-Stahl, für Sechskantmuttern DIN 7440, vollisoliert, 2-Farb-Tauchisolation - außen rot/innen gelb

⚠ 1000 V IEC 60900:2004



Art. Nr.	SW	SftL	Griff	kg	VE
110000	10	200	160	0,300	1
110002	11	200	160	0,315	1
110004	12	200	160	0,320	1
110006	13	200	160	0,320	1
110008	14	200	160	0,426	1
110010	17	200	160	0,401	1
110012	19	200	160	0,430	1
110022	11	300	160	0,429	1
110024	12	300	160	0,375	1
110026	13	300	160	0,380	1
110028	14	300	160	0,385	1
110030	17	300	160	0,534	1
110032	19	300	160	0,556	1
110034	22	300	160	0,662	1
110036	24	300	160	0,990	1

Kreuzschlüssel 1000 V

aus Chrom-Vanadium-Stahl, keine Berührung der Sechskanteinsätze untereinander, vollisoliert, 2-Farb-Tauchisolation - außen rot/innen gelb

⚠ 1000 V IEC 60900:2004



Art. Nr.	SW	SftL	kg	VE
110070	10-11-14-17	200	0,451	1
110074	11-12-13-17	200	0,225	1
110076	10-13-14-17	200	0,455	1
110078	11-13-14-17	200	0,449	1
110080	13-17-19-22	200	0,502	1

Gegenhalter 1000 V

aus Chrom-Vanadium-Stahl (31 CrV 3), 2-Farb-Tauchisolation - außen rot/innen gelb

⚠ 1000 V IEC 60900:2004



Art. Nr.	SW	GL	kg	VE
110081	10	200	0,118	1
110083	12	200	0,120	1
110084	13	200	0,140	1
110085	14	250	0,150	1
110087	16	260	0,249	1
110089	17	270	0,255	1
110091	18	265	0,250	1
110093	19	270	0,275	1
110095	20	275	0,300	1
110097	22	275	0,300	1
110099	24	270	0,350	1

Winkelschraubendreher 1000 V

aus Chrom-Vanadium-Stahl, für Innensechskantschrauben, speziell für Kabelzweigklemmringe, vollisoliert, 2-Farb-Tauchisolation - außen rot/innen gelb

⚠ 1000 V IEC 60900:2004



Art. Nr.	SW	kg	VE
110042	3	0,016	1
110044	4	0,029	1
110046	5	0,045	1
110048	6	0,051	1
110050	8	0,103	1
110052	10	0,220	1
110054	12	0,352	1

Quergriffschraubendreher 1000 V

aus Chrom-Vanadium-Stahl, für Schrauben mit Innensechskant, vollisoliert, 2-Farb-Tauchisolation - außen rot/innen gelb



⚠ 1000 V IEC 60900:2012



Art. Nr.	SW	kg	VE
110060	5	0,222	1
110062	6	0,227	1
110064	8	0,224	1

Einmaulgabelschlüssel 1000 V

aus Chrom-Vanadium-Stahl, vollisoliert, Maulstellung 15°, 2-Farb-Tauchisolation - außen rot/innen gelb



⚠ 1000 V IEC 60900:2012



Art. Nr.	SW	GL	Stärke	kg	VE
110260	6	75	3	0,021	1
110262	7	80	3,5	0,020	1
110264	8	85	3,5	0,032	1
110266	9	100	4	0,035	1
110268	10	120	5	0,035	1
110270	11	130	5,5	0,044	1
110272	12	140	5,5	0,064	1
110274	13	155	6	0,061	1
110276	14	170	6	0,084	1
110278	17	185	6,5	0,121	1
110280	19	210	7,5	0,140	1
110282	22	230	8,5	0,215	1
110284	24	250	9,5	0,242	1
110286	27	290	11,5	0,338	1
110288	30	345	13	0,390	1
110290	32	350	15	0,503	1

Einmaulgabelschlüssel-Werkzeugsatz 1000 V

in Rolltasche aus schwarzem Kunstleder, **Inhalt:** 8 Einmaulgabelschlüssel aus Chrom-Vanadium-Stahl, vollisoliert, Maulstellung 15°, 2-Farb-Tauchisolation - außen rot/innen gelb in Rolltasche Art. Nr. 220002.

Inhalt:

- Schlüsselweite: 10, 11, 12, 13, 14, 17, 19, 22



1000 V IEC 60900:2012



Art. Nr.	Satz	leer	kg	VE
220017	8-teilig	220002	1,181	1



Ringschlüssel 1000 V

aus Chrom-Vanadium-Stahl, vollisoliert, Maulstellung 75°, 2-Farb-Tauchisolation - außen rot/innen gelb



1000 V IEC 60900:2012



Art. Nr.	SW	GL	kg	VE
110300	6	140	0,061	1
110302	7	140	0,066	1
110304	8	150	0,084	1
110306	9	155	0,066	1
110308	10	160	0,092	1
110310	11	170	0,089	1
110312	12	180	0,130	1
110314	13	195	0,132	1
110316	14	205	0,147	1
110318	17	240	0,233	1
110320	19	260	0,236	1
110322	22	280	0,345	1
110324	24	280	0,357	1

Ratschen-Ringschlüssel 1000 V

2-Farb-Tauchisolation - außen rot/innen gelb

1000 V IEC 60900:2012



72 Zähne

Art. Nr.	SW	kg	VE
110870	8	0,032	1
110872	9	0,040	1
110874	10	0,050	1
110876	11	0,059	1
110878	12	0,065	1
110880	13	0,076	1
110882	14	0,086	1
110884	15	0,105	1
110886	16	0,130	1
110888	17	0,161	1
110890	18	0,179	1
110892	19	0,215	1

Rollgabelschlüssel DIN 3117 A 1000 V

aus Stahl geschmiedet, 2-Farb-Tauchisolation - außen rot/innen gelb

1000 V IEC 60900:2012



Art. Nr.	SW max.	GL	kg	VE
110555	26	200	0,325	1
110556	31	250	0,512	1
110557	36	300	0,809	1

haupa[®]

... Lösungen, die überzeugen