RoHS

Al-Cu reducing connectors

DIN

- for connections with tension relief of Al/Cu conductors to DIN 28201
- Material: Al 99,5%, DIN 40501, E-Cu DIN 40500
- Surface: bare pickled • including contact grease



Al.Cu



Art. no.	CSS rm/sm	rm/sm CU	se	TL	Cu	Al	Id./Cu	Id./Al	kg/100		PU
293578	**25**	**16**	35	61	5,5	7,6	8	12	1,600		10
293582	**35**	**16**	50	71	5,5	8,0	8	14	2,100		10
293584		**25**		71	7,0	8,0	10	14	2,500		10
293598	**50**	**25**	70	71,5	7,0	9,8	10	16	3,100		10
293600		**35**		71,5	8,2	9,8	12	16	3,300		10
293606	**70**	**25**	95	79	7,0	11,2	10	18	4,400		10
293608		**35**		79	8,2	11,2	12	18	5,500		10
293610		**50**		85	10,0	11,2	14	18	5,700		10
293622	**95**	**35**	120	79	8,2	13,2	12	22	6,000		5
293624		**50**		85	10,0	13,2	14	22	8,900		5
293626		**70**		87	11,5	13,2	16	22	8,200		5
293634	**120**	**50**	150	87	10,0	14,7	14	22	7,900		5
293636		**70**		89	11,5	14,7	16	22	9,500		5
293638		**95**		97	13,5	14,7	18	22	10,000		5
293652	**150**	**95**	185	107,5	13,5	16,3	18	25	11,700		5
293654		**120**		107,5	15,5	16,3	20	25	14,200		5
293656		**150**		124,0	17,5	16,3	22	25	16,700		5
293664	**185**	**120**	240	108	15,5	18,3	20	28	16,930		5
293666		**150**		113	17,0	18,3	22	28	19,500		5
293678	**240**	**150**	300	124	17,0	21,0	22	32	23,300		5
293680		**185**		127	19,0	21,0	25	32	25,500		5
293688	**300**	**185**	400	128	18,5	19,0	25	34	32,700		5
293690		**240**		128	21,5	23,5	28	34	37,500		5

Cupal washer

- Compound material made from aluminium and copper
- Galvanic isolation between Cu and Al
- Processing only in a dry environment
- Al-sided plated with Cu



Al.Cu

Art. no.	Ø	s1		kg/100		PU
293810	10	1		11,100		50
293812	12	2		11,100		50
293814	14	2		11,100		50
293816	16	2		11,100		50

PU Packing unit PE Price unit

The legend for abbreviations for all table headers can be found sorted alphabetically on page 408.