

Electrical insulating tape



INFO

Electro insulating tape

Typical uses in electrical installations

Insulation, Sealing, Padding, Protection from corrosion, heat, electromagnetic faults, cable marking, etc

Benefits:

- VDE tested
- DIN EN 60454-3-1
- Easy to unroll
- Very good adhesive properties
- High flexibility
- Wrinkle free adhesion to uneven surfaces
- Tear-proof and resistant to aging
- Flame retardant
- Self-extinguishing
- Temperature resistant from -30°C to 105°C
- Water, weather and UV resistant
- With many uses
- For insulating, bundling, marking
- Available in 10 colours

Electrical insulating tape "HUPtape-15"

Material: PVC, in tested VDE quality, in accordance with DIN EN 60454-3-1, flame retardant, self-extinguishing. Temperature resistant from -30°C to 105°C, water, weather and UV resistant. Highly flexible with very good adhesive properties, versatile in its uses, tear-resistant and durable, for insulating, bundling and marking. Available in ten colours.



Art. no.	widht/mm	length/m	strength	kg	PU
263800	15	10	0,15	0,035	120 10
263802	15	10	0,15	0,035	120 10
263804	15	10	0,15	0,035	120 10
263806	15	10	0,15	0,035	120 10
263808	15	10	0,15	0,035	120 10
263810	15	10	0,15	0,035	120 10
263812	15	10	0,15	0,035	120 10
263814	15	10	0,15	0,035	120 10
263816	15	10	0,15	0,035	120 10
263818	15	10	0,15	0,035	120 10

Art. no.	widht/mm	length/m	strength	kg	PU
263822	15	20	0,15	0,060	60 10
263824	15	20	0,15	0,060	60 10
263826	15	20	0,15	0,060	60 10
263828	15	20	0,15	0,060	60 10
263830	15	20	0,15	0,060	60 10
263832	15	20	0,15	0,060	60 10
263834	15	20	0,15	0,060	60 10
263836	15	20	0,15	0,060	60 10
263838	15	20	0,15	0,060	60 10
263840	15	20	0,15	0,060	60 10

Electro insulating tape

Art. no.	widht/mm	length/m	strength	kg	PU
263842	19	20	0,15	0,076	48 8
263844	19	20	0,15	0,076	48 8
263846	19	20	0,15	0,076	48 8
263848	19	20	0,15	0,076	48 8
263850	19	20	0,15	0,076	48 8
263852	19	20	0,15	0,076	48 8
263854	19	20	0,15	0,076	48 8
263856	19	20	0,15	0,076	48 8
263858	19	20	0,15	0,076	48 8
263860	19	20	0,15	0,076	48 8

Art. no.	widht/mm	length/m	strength	kg	PU
263902	19	25	0,15	0,084	48 8
263904	19	25	0,15	0,084	48 8
263906	19	25	0,15	0,084	48 8
263908	19	25	0,15	0,084	48 8
263910	19	25	0,15	0,084	48 8
263912	19	25	0,15	0,084	48 8
263914	19	25	0,15	0,084	48 8
263916	19	25	0,15	0,084	48 8
263918	19	25	0,15	0,084	48 8
263920	19	25	0,15	0,084	48 8

Art. no.	widht/mm	length/m	strength	kg	PU
263862	25	20	0,15	0,100	36 6
263864	25	20	0,15	0,100	36 6
263866	25	20	0,15	0,100	36 6
263868	25	20	0,15	0,100	36 6
263870	25	20	0,15	0,100	36 6
263872	25	20	0,15	0,100	36 6
263874	25	20	0,15	0,100	36 6
263876	25	20	0,15	0,100	36 6
263878	25	20	0,15	0,100	36 6
263880	25	20	0,15	0,100	36 6

Art. no.	widht/mm	length/m	strength	kg	PU
263882	19	33	0,15	0,120	48 8
263884	19	33	0,15	0,120	48 6
263886	19	33	0,15	0,120	48 6
263888	19	33	0,15	0,120	48 6
263890	19	33	0,15	0,120	48 6
263892	19	33	0,15	0,120	48 6
263894	19	33	0,15	0,120	48 6
263896	19	33	0,15	0,120	48 6
263898	19	33	0,15	0,120	48 6
263900	19	33	0,15	0,120	48 6

Rainbow-Pack

- VDE tested
- DIN EN 60454-3-1
- Water, weather and UV resistant



Art. no.	widht/mm	length/m	strength	PU
263820	15	10	0,15	10-pieces 1
263861	19	20	0,15	10-pieces 1

Electro insulating tape

Self-welding

Cold-resistant insulation tape "HUPtape-22plus"

- Excellent wrapping properties
- Can be processed even at very low temperatures
- Extreme weather proof (UV resistant)
- Resistant to corrosion, acids and lyes
- Processing temperature: -18°C to + 60°C
- Individually packaged in plastic box



Art. no.	TL	widht/mm	strength	kg	PU
263930	20 m	19	0,215	0,105	1

Self-welding

Self-welding insulation tape "HUPtape76seal"

- Forms homogenous welding wraps
- Excellent dielectric properties
- Weather proof (UV resistant)
- Insulation on medium voltage cables up to 69 kV
- Resistant to corrosion, acids and lyes
- Individual in box packaging



Art. no.	TL	widht/mm	strength	kg	PU
263940	9 m	19	0,76	0,203	1

haupa[®]

... convincing solutions

Germany: **HAUPA**, Koenigstr. 165-169, 42853 Remscheid, Phone: +49 (0)2191 8418-0, Fax: +49 (0)2191 8418-840, sales@haupa.com