

Al compression cable lugs


DIN

- Material: Al 99,5% • Surface: bare • Tube dimension to DIN 46329
- With marks for correct crimping
- For non-tension connections of Al-cables DIN 48201, part 1 and DIN EN 50182
- For pre-rounded sm/se sector shaped conductors • including contact grease



Al

Art. no.	CSS rm/sm	se	M	ld.	d2	d1	v1	v2	l	B	kg/100	PU
292904	16	25	8	12	8,5	5,8	4	2	52,0	18,0	1,400	50
292906			10	12	10,5	5,8	4	2	52,0	18,0	1,400	50
292908	25	35	8	12	8,5	6,8	4	2	60,0	18,0	1,400	50
292910			10	12	10,5	6,8	4	2	60,0	18,0	1,400	50
292912	35	50	10	14	10,5	8,0	5	2	67,0	21,0	2,100	50
292914			12	14	13,0	8,0	5	2	67,0	21,0	2,000	50
292916	50	70	10	16	10,5	9,8	5	2	72,0	25,0	2,700	50
292918			12	16	13,0	9,8	5	2	72,0	25,0	2,700	50
292920	70	95	10	18	10,5	11,2	6	3	86,0	28,0	4,400	40
292922			12	18	13,0	11,2	6	3	86,0	28,0	4,200	40
292924	95	120	10	22	10,5	13,2	6	3	90,0	32,0	6,300	25
292926			12	22	13,0	13,2	6	3	90,0	32,0	6,400	30
292928			16	22	17,0	13,2	6	3	90,0	34,0	6,400	25
292930	120	150	12	22	13,0	14,7	6	3	91,0	32,0	6,700	25
292932			16	22	17,0	14,7	6	3	91,0	34,0	7,000	25
292934	150	185	12	25	13,0	16,3	6	3	103,0	35,0	9,400	20
292936			16	25	17,0	16,3	6	3	103,0	35,0	8,300	20
292938			20	25	21,0	16,3	6	3	103,0	41,0	9,100	20
292940	185	240	12	28	13,0	18,3	6	3	106,0	40,0	11,700	15
292942			16	28	17,0	18,3	6	3	106,0	40,0	11,600	15
292944			20	28	21,0	18,3	6	3	106,0	40,0	12,000	15
292946	240	300	12	32	13,0	21,0	8	3	116,0	45,0	16,900	10
292948			16	32	17,0	21,0	8	3	116,0	45,0	16,900	12
292950			20	32	21,0	21,0	8	3	116,0	45,0	16,200	10



Al compression cable lugs acc. to DIN 46329


DIN

- Material: Al 99,5% • Surface: bare • Design with oil stop
- Tube dimension to DIN 46329 • With marks for correct crimping
- For non-tension connections of Al-cables DIN 48201, part 1 and DIN EN 50182
- For pre-rounded sm/se sector shaped conductors • Including contact grease



Al

Art. no.	CSS rm/sm	se	M	ld.	d2	d1	v1	v2	l	B	kg/100	PU
292770	35	50	10	14	10,5	8,0	5	2	62,0	25,0	2,000	50
292772			12	14	13,0	8,0	5	2	62,0	25,0	2,000	50
292774	50	70	10	16	10,5	9,8	5	2	62,0	25,0	2,800	50
292776			12	16	13,0	9,8	5	2	62,0	25,0	2,600	50
292778	70	95	10	18	10,5	11,2	6	3	72,0	25,0	3,900	25
292780			12	18	13,0	11,2	6	3	72,0	25,0	3,500	25
292782	95	120	10	22	10,5	13,2	6	3	75,0	25,0	5,900	25
292784			12	22	13,0	13,2	6	3	75,0	25,0	5,600	25
292786	120	150	12	22	13,0	14,7	6	3	80,0	30,0	6,400	25
292788			16	22	17,0	14,7	6	3	80,0	30,0	6,600	25
292790	150	185	10	25	10,5	16,3	6	3	90,0	30,0	8,400	25
292792			12	25	13,0	16,3	6	3	90,0	30,0	8,300	25
292794			16	25	17,0	16,3	6	3	90,0	30,0	8,200	20
292796	185	240	10	28	10,5	18,3	6	3	91,0	30,0	10,400	20
292798			12	28	13,0	18,3	6	3	91,0	30,0	10,500	20
292800			16	28	17,0	18,3	6	3	91,0	30,0	12,000	20
292802	240	300	12	32	13,0	21,0	8	3	103,0	38,0	16,100	10
292804			16	32	17,0	21,0	8	3	103,0	38,0	15,900	10
292806			20	32	21,0	21,0	8	3	103,0	38,0	15,200	10
292808	300	-	12	34	13,0	23,3	8	3	103,0	38,0	17,200	10
292810			16	34	17,0	23,3	8	3	103,0	38,0	18,500	10
292812			20	34	21,0	23,3	8	3	103,0	38,0	17,300	10
292814	400	-	12	38	13,0	26,0	-	4	116,0	38,0	24,700	10
292816			16	38	17,0	26,0	-	4	116,0	38,0	23,000	10
292818			20	38	21,0	26,0	-	4	116,0	38,0	23,500	10
292820	500	-	12	44	13,0	29,0	-	4	122,0	44,0	43,600	6
292822			16	44	17,0	29,0	-	4	155,0	44,0	33,200	6
292824			20	44	21,0	29,0	-	4	122,0	44,0	43,000	6



haupa®

...convincing solutions

Germany: HAUPA, Koenigstr. 165-169, 42853 Remscheid, Phone: +49 (0)2191 8418-0, Fax: +49 (0)2191 8418-840, sales@haupa.com

Al-Crimp connector DIN 46267 Part 2

DIN

- Material: Al 99,5% • Surface: bare • Design with oil stop
- Manufactured DIN 46267, part 2 • With marks for correct crimping
- For non-tension connections of Al conductors to DIN 48201, DIN EN 50182
- For pre-rounded sm/se sector shaped conductors • Including contact grease



Al

Art. no.	CSS mm/sm	se	d1	v1	v2	TL	ld./Al	kg/100		PU
293542	25	35	6,8	8	4	70	12	1,600		100
293544	35	50	8,0	10	4	85	14	2,700		100
293546	50	70	9,8	10	4	85	16	3,300		50
293548	70	95	11,2	12	6	105	18	5,800		50
293550	95	120	13,2	12	6	105	22	8,200		25
293552	120	150	14,7	12	6	105	22	7,900		25
293554	150	185	16,3	12	6	125	25	11,500		25
293556	185	240	18,3	12	6	125	28	12,300		20
293558	240	300	20,0	16	6	145	32	21,200		15

