

INFO

Hole saws

Industrial quality

The performance of a saw blade depends on the base material quality, the kind of toothing and the tooth geometry. These factors guarantee in conjunction with the correct use of the machine and blade selection the optimum result in cutting all materials.

- Above average concentricity
- Even cutting performance
- Extremely quiet operation even at high speeds
- True diameter
- High resistance even with high loads and torques
- Fast progress thanks to aggressive and permanently sharp cutting performance
- Highest lifetime even with very hard materials such as cast and stainless steel

T.C.T. Hole Saw

High concentricity and smooth cutting through strong construction. Precise and clean cut. Large tungsten carbide inserts for reshaping and long lifetime. Hole saw comes complete with shank, drill bit, ejector spring and allen key. Long lifetime. **Especially for:** Flat materials of steel, cast steel, stainless steel (up to 4 mm), Chrome-nickel Steel (up to 2 mm), non-ferrous metals, glassfibre and carbon-fibre reinforced products (CRP, GRP), epoxy, reinforced textures and sandwich-materials (up to 6 mm).



Art. no.	Ø	ST	Bohrer-Ø	kg	PU
392100	16	12	6,5	0,095	1
392102	20	31	6,5	0,115	1
392104	22	31	6,5	0,135	1
392106	22,5	31	6,5	0,155	1
392108	25	31	6,5	0,175	1
392110	30	31	6,5	0,195	1
392112	32	31	6,5	0,215	1
392114	35	31	6,5	0,235	1
392116	40	31	6,5	0,255	1
392118	50	31	6,5	0,275	1
392120	60	31	6,5	0,295	1

Hollow saws

T.C.T. center drill for hole saw arbors



Art. no.	TL	Ø	kg	PU
392122	100	6,5	0,020	1

Spring for hole saw arbors



Art. no.	spring	kg	PU
392124		0,005	1

T.C.T. Hole Saw Fastcut

Very fast and aggressive cut in wood due to large exhaust slots. **Especially for:** wood materials up to 60 mm.



Art. no.	Ø/Inch	Ø	ST	Bohrer-Ø	kg	PU
231942	3/4	19	50	6,35	0,047	1
231944	7/8	22	50	6,35	0,062	1
231946	1	25	50	6,35	0,077	1
231948	1 1/6	27	50	6,35	0,092	1
231950	1 3/16	30	50	6,35	0,115	1
231952	1 1/4	32	50	6,35	0,122	1
231954	1 3/8	35	50	6,35	0,133	1
231956	1 9/16	40	50	6,35	0,123	1
231958	1 3/4	44	50	6,35	0,144	1
231960	2	51	50	6,35	0,179	1
231962	2 1/8	54	50	6,35	0,198	1
231964	2 3/8	60	50	6,35	0,206	1
231966	2 1/2	64	50	6,35	0,267	1
231968	2 9/16	65	50	6,35	0,279	1
231970	2 11/16	68	50	6,35	0,275	1
231972	2 3/4	70	50	6,35	0,316	1
231973	2 7/8	73	50	6,35	0,296	1
231974	3	76	50	6,35	0,298	1
231976	3 1/8	79	50	6,35	0,379	1
231978	3 1/4	83	50	6,35	0,428	1
231980	4	102	50	6,35	0,591	1
231982	4 1/2	114	50	6,35	0,773	1

haupa®

...convincing solutions

Germany: HAUPA, Koenigstr. 165-169, 42853 Remscheid, Phone: +49 (0)2191 8418-0, Fax: +49 (0)2191 8418-840, sales@haupa.com

Hollow saws

Bi-Metal Hole Saws 10 tpi

8% Cobalt

Finely toothed, 10 tpi, made of high quality, cobalt-alloyed bi-metal for clean and fast cuts and a long lifetime. Massive back plate ensures a smooth cut and precise holes for threads, cable and pipe lead-throughs. **Especially for:** steel and stainless steel, sheet metal up to 1 mm.



Art. no.	Ø	ST	Bohrer-Ø	kg	PU
392050	16	31	6,5	0,036	1
392052	19	31	6,5	0,039	1
392054	20	31	6,5	0,046	1
392056	21	31	6,5	0,052	1
392058	22	31	6,5	0,055	1
392060	24	31	6,5	0,059	1
392062	25	31	6,5	0,064	1
392064	29	31	6,5	0,070	1
392066	30	31	6,5	0,077	1
392068	32	31	6,5	0,081	1
392070	38	31	6,5	0,092	1
392072	40	31	6,5	0,098	1

Hole saw with edge countersink and board ejector

For setting wall-flush sockets, Ø 68 mm

- Cutting depth 40 mm
- High concentricity
- Specially for plasterboard, softwood, plywood, Fermacell etc.
- 11 mm hexagonal holder
- In plastic box



Art. no.	Ø/Inch	Ø	Bohrer-Ø	ST	kg	PU
231929	2 11/16	68	6,35	35	0,360	1

Bi-Metal Hole Saws 4 - 6 tpi

8% Cobalt

Variable toothing of 4 - 6 tpi and high quality, cobaltalloyed bi-metal for clean and fast cuts and a long lifetime. Massive back plate ensures a smooth cut and precise holes for sockets, threads, cable and pipe lead-throughs. **Especially for:** Wood, gypsum board, plastics, non-ferrous metals, aluminium steel and stainless steel minimum 1 mm. Special cutting depth on request.



Art. no.	Ø/Inch	Ø	ST	Bohrer-Ø	kg	PU
231803	9/16	14	35	6,35	0,036	1
231900	3/4	19	35	6,35	0,036	1
231901/21		21	30	6,5	0,050	1
231902	7/8	22	35	6,35	0,046	1
231904	1	25	35	6,35	0,071	1
231904/29		29	30	6,5	0,050	1
231906	1 1/6	27	35	6,35	0,075	1
231908	1 3/16	30	35	6,35	0,079	1
231910	1 1/4	32	35	6,35	0,085	1
231912	1 3/8	35	35	6,35	0,092	1
231912/38		38	30	6,5	0,050	1
231914	1 9/16	40	35	6,35	0,086	1
231914/46		46	30	6,5	0,050	1
231916	1 3/4	44	35	6,35	0,105	1
231918	2	51	35	6,35	0,133	1
231920	2 1/8	54	35	6,35	0,145	1
231922	2 3/8	60	35	6,35	0,168	1
231924	2 1/2	64	35	6,35	0,192	1
231926	2 9/16	65	35	6,35	0,198	1
231928	2 11/16	68	35	6,35	0,214	1
231930	2 3/4	70	35	6,35	0,223	1
231931	2 7/8	73	35	6,35	0,236	1
231932	3	76	35	6,35	0,253	1
231934	3 1/8	79	35	6,35	0,275	1
231936	3 1/4	83	35	6,35	0,304	1
231938	4	102	35	6,35	0,429	1
231939/111		111	30	6,5	0,050	1
231940	4 1/2	114	35	6,35	0,549	1
231940/127		127	30	6,5	0,050	1
231940/152		152	30	6,5	0,650	1
231940/210		210	30	6,5	0,850	1

Adapter for hollow saws

INFO

Professional Quick Release System for Hole Saws

- Change quickly in seconds between the different diameters and various types of hole saws.
- One arbor for all diameters between 14 - 210 mm.
- Absolute concentricity and diameter true to size.
- Compact "heavy duty" design for highest demands and very long life.
- No time-consuming seizing up of the hole saw onto the thread of the arbor.
- Runs two hole saws at the same time. A smaller diameter guides as a centering aid when enlarging already existing holes.
- Fits all standard hole saw brands.*



*With 1/2" (20 UNF) or 5/8" (18 UNF) thread.

Quick change holder for hole saws, "RE-LOAD"

RE-LOAD

for all diameters from 14-210 mm, 9.5 mm hexagonal shank



Art. no.	size	shankt/Ø	kg	PU
392010	14 - 210	9,5	0,100	1

Adapter assortment for holder, "RE-LOAD"

RE-LOAD



Art. no.	set	kg	PU
392012	5 x Ø 14-30 mm	0,100	1
392014	5 x Ø 32-210 mm	0,075	1
392016	2 x Ø 14-30 mm, 3 x Ø 32-210 mm	0,065	1

Adapter assortment for hole enlarger "RE-LOAD"

RE-LOAD

1 x Ø 14 - 30 mm, 1 x Ø 32 - 210 mm



Art. no.	size	shankt/Ø	kg	PU
392018	14 - 210	9,5	0,050	1

Centre drill for holder, "RE-LOAD"

RE-LOAD



Art. no.	TL	Ø	kg	PU
392020	100	6,5	0,030	1
392022	100	6,5	0,030	1

Hex shank with plug ejection

hexagon shank



Art. no.	size	shankt/Ø	kg	PU
392028	32 - 210	9,5	0,050	1

SDS-shank

hexagon shank, 11 mm (14 - 30 mm)



Art. no.	size	shankt/Ø	kg	PU
392024	14 - 30	11	0,050	1

SDS-shank

hexagon shank, 11 mm (32 - 210 mm)



Art. no.	size	shankt/Ø	kg	PU
392026	32 - 210	11	0,050	1

Adapter "QuickLock"

hexagon shank



Art. no.	size	shank	kg	PU
231998	14-30	hexagon	0,067	1
231999	32-152	hexagon	0,107	1

Centre drills for 231998 / 231999



Art. no.	TL	type	Ø	shank	kg	PU
232007	120	universal	9	hexagon	0,020	1

haupa[®]

...convincing solutions

Hollow saws

Bi-metal hole saw set

RE-LOAD

Set in black plastic case, dimensions: 255 x 210 x 72 mm

Contents:

- Hole saws bi-metal 35 mm
- Hole saws bi-metal 68 mm
- Hole saws bi-metal 76 mm
- Quick change holder for hole saws "RE-LOAD"
- 3 adapters for holder "RE-LOAD" 32 - 210 mm



Art. no.	Content	kg	PU
231984	3-pieces	1,300	1

