

Cable lugs acc. to DIN 46235

DIN

- Material: 99,9% E-Cu DIN 40500
- Tube dimension acc. to DIN 46235 • Surface: tin-plated
- With marks for correct crimping
- Annealed material for easier crimping



Cu

Art. no.	CSS	M	ld.	d2	d1	d4	A	v1	v2	l	c1	c2	B	kg/100	PU	PU
290404	6	6	5	6,4	3,8	5,5	10,0	2	-	24,0	7,5	8,0	8,5	0,300	800	100
290406		8	5	8,4	3,8	5,5	10,0	2	-	24,0	10,0	10,0	13,0	0,300	800	100
290408	10	5	6	5,3	4,5	6,0	10,0	2	-	27,0	7,0	8,5	9,0	0,400	800	100
290410		6	6	6,4	4,5	6,0	10,0	2	-	27,0	7,5	8,5	9,0	0,400	800	100
290412		8	6	8,4	4,5	6,0	10,0	2	-	27,0	10,0	10,0	13,0	0,400	800	100
290414		10	6	10,5	4,5	6,0	10,0	2	-	28,0	10,0	10,0	15,0	0,400	800	100
290416	16	6	8	6,4	5,5	8,5	20,0	2	1	36,0	7,5	8,0	13,0	1,200	500	50
290418		8	8	8,4	5,5	8,5	20,0	2	1	36,0	10,0	10,0	13,0	1,200	400	50
290420		10	8	10,5	5,5	8,5	20,0	2	1	36,0	12,0	12,0	17,0	1,100	400	50
290422		12	8	13,0	5,5	8,5	20,0	2	1	36,0	13,0	13,0	18,0	1,200	400	50
290424	25	6	10	6,4	7,0	10,0	20,0	2	1	38,0	7,5	8,0	14,0	1,300	300	50
290426		8	10	8,4	7,0	10,0	20,0	2	1	38,0	10,0	10,0	16,0	1,400	300	50
290428		10	10	10,5	7,0	10,0	20,0	2	1	38,0	12,0	12,0	17,0	1,600	300	50
290430		12	10	13,0	7,0	10,0	20,0	2	1	38,0	13,0	13,0	19,0	1,500	300	50
290432	35	6	12	6,4	8,2	12,5	20,0	2	1	42,0	7,5	8,0	17,0	2,700	150	25
290434		8	12	8,4	8,2	12,5	20,0	2	1	42,0	10,0	10,0	17,0	2,900	150	25
290436		10	12	10,5	8,2	12,5	20,0	2	1	42,0	12,0	12,0	19,0	2,900	150	25
290438		12	12	13,0	8,2	12,5	20,0	2	1	42,0	13,0	13,0	21,0	2,700	150	25
290440	50	8	14	8,4	10,0	14,5	28,0	3	1	52,0	10,0	10,0	20,0	4,400	100	25
290442		10	14	10,5	10,0	14,5	28,0	3	1	52,0	12,0	12,0	22,0	4,500	100	25
290444		12	14	13,0	10,0	14,5	28,0	3	1	52,0	13,0	13,0	24,0	4,400	100	25
290446		16	14	17,0	10,0	14,0	28,0	3	1	52,0	16,0	16,0	28,0	4,200	100	20
290448	70	8	16	8,4	11,5	16,5	28,0	3	1	55,0	10,0	10,0	24,0	5,900	100	25
290450		10	16	10,5	11,5	16,5	28,0	3	1	55,0	12,0	12,0	24,0	5,900	100	25
290452		12	16	13,0	11,5	16,5	28,0	3	1	55,0	13,0	13,0	24,0	5,900	100	25
290454		16	16	17,0	11,5	16,5	28,0	3	1	55,0	16,0	16,0	30,0	5,800	80	20
290456	95	10	18	10,5	13,5	19,0	35,0	4	2	65,0	12,0	12,0	28,0	8,800	60	15
290458		12	18	13,0	13,5	19,0	35,0	4	2	65,0	13,0	13,0	28,0	8,900	60	15
290460		16	18	17,0	13,5	19,0	35,0	4	2	65,0	16,0	16,0	32,0	8,700	60	15
290462	120	10	20	10,5	15,5	21,0	35,0	4	2	70,0	15,0	16,0	32,0	11,000	40	20
290464		12	20	13,0	15,5	21,0	35,0	4	2	70,0	16,0	17,0	32,0	11,100	40	20
290466		16	20	17,0	15,5	21,0	35,0	4	2	70,0	19,0	20,0	32,0	10,500	40	20
290468		20	20	21,0	15,5	21,0	35,0	4	2	70,0	21,0	22,0	38,0	11,300	25	15
290470	150	10	22	10,5	17,0	23,5	35,0	4	2	78,0	15,0	16,0	34,0	15,600	30	15
290472		12	22	13,0	17,0	23,5	35,0	4	2	78,0	16,0	17,0	34,0	15,700	30	15
290474		16	22	17,0	17,0	23,5	35,0	4	2	78,0	19,0	20,0	34,0	15,900	30	15
290476		20	22	21,0	17,0	23,5	35,0	4	2	78,0	21,0	22,0	40,0	16,000	25	15
290478	185	10	25	10,5	19,0	25,5	40,0	4	2	82,0	15,0	16,0	37,0	18,000	24	10
290480		12	25	13,0	19,0	25,5	40,0	4	2	82,0	16,0	17,0	37,0	18,400	24	10
290482		16	25	17,0	19,0	25,5	40,0	4	2	82,0	19,0	20,0	37,0	18,400	24	10
290484		20	25	21,0	19,0	25,5	40,0	4	2	82,0	21,0	22,0	40,0	17,700	20	10
290486	240	12	28	13,0	21,5	29,0	40,0	5	2	92,0	16,0	17,0	42,0	26,500	16	8
290488		16	28	17,0	21,5	29,0	40,0	5	2	92,0	19,0	20,0	42,0	26,600	16	8
290490		20	28	21,0	21,5	29,0	40,0	5	2	92,0	21,0	22,0	45,0	27,600	10	8
290492	300	16	32	17,0	24,5	32,0	50,0	-	2	100,0	19,0	22,0	46,0	34,300	10	5
290494		20	32	21,0	24,5	32,0	50,0	-	2	100,0	19,0	22,0	46,0	33,100	10	5
290496	400	16	38	17,0	27,5	38,5	70,0	-	3	115,0	25,0	25,0	54,0	69,800	8	3
290498		20	38	21,0	27,5	38,5	70,0	-	3	115,0	25,0	25,0	54,0	66,400	8	1
290516	500	20	42	21,0	31,0	42,0	70,0	-	3	125,0	25,0	25,0	60,0	82,600	8	1
290518	625	20	44	21,0	34,5	44,0	80,0	-	3	125,0	25,0	25,0	64,0	79,000	6	1
290520	800	20	52	21,0	40,0	52,0	100,0	-	3	165,5	30,0	30,0	75,0	139,400	10	1
290522	1000	20	58	21,0	44,0	58,0	100,0	-	3	165,0	30,0	30,0	83,0	195,000	10	1

